

CMR SERIES



CMR CONDENSER MICROPHONES

18mm gold-plated diaphragm
Matte-Chrome Housing

The CMR condenser microphone with a uniform sound frequency response, very good front-to-rear attenuation, low noise, guarantee of perfect crystal clear sound throughout the entire acoustic spectrum.

The CMR microphone uses gold plated diaphragm (diameter of 18mm) installed in a housing made out of brass, electroplated with matte nickel or powder coated in black.

The CMR microphone is equipped with a sliding switch and a signaling diode and a cable with XLR connector.

This series is made in ultra-hard and long-lasting housing.



GENERAL SPECIFICATION

Technical Data	CMR/45	CMR/50	CMR/55	CMR/60	CMR/65	CMR/70	CMR75
Frequency response	20Hz-20kHz z	20Hz-20kHz	20Hz-20kHz z	20Hz-20kHz z	20Hz-20kHz z	20Hz-20kHz z	20Hz-20kHz z
Sensitivity at 1kHz	26 mV/Pa	26 mV/Pa	26 mV/Pa	26 mV/Pa	26 mV/Pa	26 mV/Pa	26 mV/Pa
Impedance	200Ω	200Ω	200Ω	200Ω	200Ω	200Ω	200Ω
Charactericts	supercardio id	supercardioi d	supercardio id	supercardio id	supercardio id	supercardio id	supercardio id
Phantom power	20-48V DC	20-48V DC	20-48V DC	20-48V DC	20-48V DC	20-48V DC	20-48V DC
Signal/Noise ratio (S/N)	74 dB	74 dB	74 dB	74 dB	74 dB	74 dB	74 dB
Max sound level for 0,5% THD (SPL)	134 dB	134 dB	134 dB	134 dB	134 dB	134 dB	134 dB
Wire length	5	5	5	5	5	5	5
Microphone length	45	50	55	60	65	70	75
Weight	395g	400g	405g	410g	415g	420g	425g